

## "Simple the best value in the industry"



## **FEATURES:**

- Picture shown left-hand model is standard. Right-hand model optional.
- Cutting off capacity (thickness x width):
  2" x 21", 4" x 19", 6" x 15", 8" x 8"
- Motion cycles are pneumatically operated, and conveniently controlled by a foot switch.
- 24" sawblade is included
- Convenient cutting thickness adjustment is made by means of a knob. A rule gauge is provided for correct reading of sawblade protrusion over the table.
- · Hinged guard holds workpiece securely.
- Fast cutting rate up to 40 strokes per minute. Cycle speeds are adjustable.
- Powerful, high torque 15HP (Stock machine)
- · Easy belt tension adjustment or replacement.
- Infeed and outfeed roller conveyors are optional

## **SPECIFICATIONS:**

Cutting capacity	2" x 21", 4" x 19", 6" x 15",
(thickness x width)	8" x 8"
Cycle speed	40 strokes/min
Cycle operation	Air / mechanical
Saw blade size (optional)	20" / 22" / 24"
Saw arbor diameter	1"
Saw blade speed	2400 RPM
Dust exhaust diameter	4" (100mm)
Motor	15 HP (stock machine)
Table size	45.28" x 26"
Table Size	(1150 x 660 mm)
Net weight	1058 lbs (480 kgs)
Gross weight	1433 lbs (560 kgs)
Packing dimensions	53.54" x 35.43" x 57.09"
(L x W x H)	(1360 x 900 x 1450 mm)
	,

<sup>\*</sup>Available in 230 / 460 / 575 V electrics